



Main

Range of Product	PacDrive 3
Product or Component Type	Single drive
Device short name	LXM 62

Complementary

Product compatibility	Servo motor SH3 5.51 in (140 mm), 4 optimized in terms of torque and speed Servo motor SH3 8.07 in (205 mm), 1 optimized in terms of torque and speed Servo motor SH3 8.07 in (205 mm), 2 optimized in terms of torque and speed Servo motor SH3 8.07 in (205 mm), 3 optimized in terms of torque and speed Servo motor MH3 5.51 in (140 mm), 2 optimized in terms of torque and speed Servo motor MH3 5.51 in (140 mm), 3 optimized in terms of torque and speed Servo motor MH3 7.48 in (190 mm), 1 optimized in terms of torque and speed Servo motor MH3 7.48 in (190 mm), 2 optimized in terms of torque and speed Servo motor MH3 7.48 in (190 mm), 3 optimized in terms of torque and speed Servo motor SHS
Phase	2 phases
[Us] rated supply voltage	24 V DC
Continuous output current	50 A 4 kHz
Output current 3s peak	130 A 4 kHz
Continuous power	24.7 kW
Nominal power	24.7 kW
Overvoltage category	III
Electrical connection	Terminal 0.2...15 mm ² , AWG 24...AWG 16 CN4) Terminal 0.5...16 mm ² , AWG 20...AWG 6 CN5) Terminal 0.75...16 mm ² , AWG 18...AWG 6 CN6) Terminal 0.2...6 mm ² , AWG 24...AWG 10 CN7)
Tightening torque	CN1 22.13 lbf.in (2.5 N.m)
Number of inputs	2 digital 2 touch probe
Discrete input voltage	24 V DC
Number of outputs	2 digital
Discrete output voltage	24 V DC
Safety function	STO (safe torque off)
Physical interface	SERCOS III
Net Weight	14.99 lb(US) (6.8 kg)

Environment

Standards	UL 508C EN 61800-5-1 EN/ISO 13849-1 IEC 61508 EN 61800-3 IEC 62061 EN 61800-5-2 EN 62061 EN/ISO 13849-2 CSA C22.2 No 14
Product Certifications	CSA UL CE EAC TÜV
IP degree of protection	IP20 EN/IEC 60529
Vibration resistance	10 m/s² EN/IEC 60721-3-3
Shock resistance	100 m/s² EN/IEC 60721-3-3
Pollution degree	2 EN/IEC 61800-5-2
Environmental characteristic	3K3 IEC 60721-3-3
Relative humidity	5...85 %
Ambient Air Temperature for Operation	41...131 °F (5...55 °C)

Ordering and shipping details

Category	18356-PACDRIVE3 LEXIM62 SERVO DRIVES
Discount Schedule	PC52
GTIN	3606485313399
Nbr. of units in pkg.	1
Package weight(Lbs)	16.63 lb(US) (7.545 kg)
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.28 in (18.5 cm)
Package 1 width	13.19 in (33.5 cm)
Package 1 Length	17.91 in (45.5 cm)
Unit Type of Package 2	P06
Number of Units in Package 2	6
Package 2 Weight	118.54 lb(US) (53.77 kg)
Package 2 Height	30.31 in (77 cm)
Package 2 width	23.62 in (60 cm)
Package 2 Length	31.50 in (80 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes